



ALUMINIUM RAINWATER SYSTEMS

## Flowrates Cast Aluminium Gutters

**NOTE: ALL FLOW RATES QUOTED IN LITRES PER SECOND**

- Gutter capacities based on BS EN 12056-3:2000, assuming a maximum distance of 50 x gutter depth, from high point to outlet.
- Longer gutters or gutters with corners exceeding 10° will have a reduced capacity.

Profile	Size	63	75	100	75x75	100x76	100x100
Half Round	100	1.14	1.24	-	1.24	1.24	-
Half Round	112	1.14	1.62	-	1.62	1.62	-
Half Round	125	1.24	2.08	-	2.08	2.08	-
Beaded Half Round	100	1.14	1.24	-	1.24	1.24	-
Beaded Half Round	112	1.62	1.62	-	1.62	1.62	-
Beaded Half Round	125	1.77	1.90	-	2.08	2.08	-
Beaded Deepflow	112	1.77	1.90	-	2.1	3.06	-
Victorian Ogee	100	1.32	1.32	-	1.32	1.32	-
Victorian Ogee	112	1.35	1.82	-	1.82	1.82	-
Victorian Ogee	125	1.35	2.12	-	2.10	2.34	-
Moulded	100x75	1.4	1.64	-	2.10	2.44	-
Moulded	125x100	1.52	1.97	3.81	2.1	4.62	4.62
Moulded	150x100	2.42	2.84	3.81	2.1	4.65	5.12

For further information contact Stormguard Rainwater Systems Technical Services

Tel: +44 (0)1625 665096  
Email: [pw@stormguard.co.uk](mailto:pw@stormguard.co.uk)

**Stormguard Rainwater Systems pursues a policy of constant product development and information contained within this datasheet is therefore subject to change without notice.**